

Enchlor manufactures a complete line of isolation valve assemblies for use with Chlorine, Sulfur dioxide and Ammonia gases. These isolation valves aid in keeping pressurized gas lines safer and easier to use. They can also be used to move the vacuum regulator away from the cylinder for ease of use or when mounting may be an issue. All Enchlor isolation valves utilize industry standard gas cylinder valves for compatibility. These valves are rated at 500 psi. maximum working pressure, are capable of up to 2,000 cycles and can be easily serviced, making them great for continuous duty and durability. All Enchlor isolating valves are Epoxy-Powder-Coated for extreme protection and durability.

IVE-116-500 Isolation Valve

The IVE-116-500 isolation valve helps to make pressurized gas lines safer and easier to use by isolating the pressurized line from the gas source. This isolation valve is primarily used in manifold systems and eliminates the need to draw down the entire system before replacing depleted gas cylinders or ton containers.

The special design of the IVE-116-500 permits 360-degree rotation of the valve to reduce stress on the flexible connector and provide ease of connection.



IVE-130-500 Isolating Valve

The IVE-130-500 is designed for use with 150 lb. cylinders, ton containers or manifold applications. It is commonly used to mount a vacuum regulator up and away from non-standard containers or to accommodate a valve shut-off actuator

